

CHARLES AUSTEN PUMPS LTD



WASTEWATER
AERATION PUMPS

CONTENTS

ABOUT US

INTRODUCTION	- Page. 3
CAPABILITIES	- Page. 4
TECHNOLOGY	- Page. 5
ORDERING	- Page. 14
WARRANTY	- Page. 14

AIR PUMPS

ENVIRO ET SERIES	- Page. 6
ENVIRO ETA SERIES	- Page. 8
ENVIRO DUAL SERIES	- Page. 10
ENVIRO ETX SERIES	- Page. 11

ACCESSORIES

DIFFUSERS	- Page. 12
ENVIROSURE ALARM	- Page. 12
MANIFOLDS	- Page. 13
TUBING	- Page. 13



NEW

DUAL PUMP COMING SOON

Allows the user to operate both aeration and water lift from one unit. The enviro dual is complete with programmable electronic interface.

WWW.CHARLESAUSTEN.COM



ABOUT US



INTRODUCTION

For almost three-quarters of a century, Charles Austen Pumps has revolutionized many different markets through its design innovation but also its world-wide distribution network, and during that time has gained the respect and trust of industries throughout.

Charles Austen Pumps Ltd stocks an extensive range of linear aeration pumps and accessories suitable for use in wastewater applications. The range incorporates air pumps with varying flow rates. All of our pumps are built with thermal cut out and safety trip switch.

UL Approval

UL Number - QDGS.E348002

UL Installation Requirements

Ordinary locations include:

Damp location - partially protected locations under canopies, marquees, roofed open porches and like locations, and interior locations subject to moderate degrees of moisture, such as some basements, barns and cold-storage warehouses.

Wet location - installations underground or in concrete slabs or masonry in direct contact with the earth, and locations subject to saturation with water or other liquids, such as vehicle washing areas, and locations exposed to weather and unprotected.

Outdoor use - in general, individual appliances and equipment have been investigated only for use indoors, in dry locations. An exception is where outdoor use is specifically permitted by the article of the NEC concerned with the product installation. See also the general guide information for the product category or included in the individual listing. In some cases of the title (eg., Snow Movers, Swimming Pool Fixtures) indicates the conditions for which the product has been investigated.

FOLLOW US:



CONTACT US:



+44 (0)1932 355277



INFO@CHARLESAUSTEN.COM



WWW.CHARLESAUSTEN.COM

3

CAPABILITIES

R&D

The Process begins in our state of the art Research and Development department. Using an array of high-tech equipment alongside the old fashioned proven methods we can accurately gauge the performance and reliability of our pumps, ensuring we are staying at the top of our game.



TOOLMAKING

With 10 members of staff dedicated solely to toolmaking, Charles Austen is proud to boast an impressive 'Tool Room' complete with a labyrinth of imposing machinery. This allows us to efficiently and precisely create the tooling we require to continue revolutionizing the pump industry.



MOULDING

Charles Austen employs modern CNC moulding machines to mould components all in-house. As a company we have invested heavily in our moulding capability to ensure high fidelity components.



ASSEMBLY

With 20,000 square foot of manufacturing lines Charles Austen Pumps efficiently constructs our pumps primarily by hand. Pumps are then tested to secure that each of them leave the factory as reliable as we designed them to be following the ISO 9001 quality standard.



WAREHOUSING

With 5 dedicated buildings on site for warehousing Charles Austen Pumps have the capacity to hold huge orders in waiting. We utilise double shifts to ensure that stock items are despatched within 24 hours.



TECHNOLOGY



**LINEAR
DIAPHRAGM**

The simple yet efficient pumping principle uses a magnetically operated diaphragm. This action flexes a diaphragm at one, or both ends of the connecting rod within a totally sealed pumping chamber. This eliminates sliding parts keeping wear, tear and power consumption to a minimum.



**GREEN DRIVE
TECHNOLOGY**

Look out for the green drive technology symbol as it means that the motor inside the pump runs efficiently with minimal power consumption. Green drive also allows the pumps to save energy without having to hamper its performance.



DURABLE DESIGN

All of our ET pumps are made with galvanised steel casings making the pumps perfect for indoor and outdoor useage. Having the steel casing means that the pump can with stand all weather conditions including sub-zero climates and high temperatures with no impact on performance.



CERTIFIED

All of our pumps have been UL tested by an independant laboratory representative who have determined that it meets UL's requirements. These requirements are often based on UL's published and nationally recognized Standards for Safety.



All Enviro® pumps are covered by a two year warranty on the pump motor. To validate this warranty, the aerator must be serviced on a yearly basis. For more information please read page 14.



enviro[®] ET SERIES PRO

110V / 230V - UK/EU/USA plug version



Model no.	Performance		Power consumption (w)	Connector Size (mm)	Dimensions (mm) (LxWxH)
	Flow (l/min)	Pressure (bar)			
ET30	30	@ 0.12	25	14	208x150x178
ET40	40	@ 0.12	30	14	218x156x182
ET60	60	@ 0.12	55	18	203x165x153
ET80	80	@ 0.10	85	18	210x185x171
ET100	100	@ 0.10	105	18	238x196x177
ET120	120	@ 0.10	125	18	265x215x198
ET150	150	@ 0.20	130	18	256x200x222
ET200	200	@ 0.20	195	18	256x200x222


- ✓ Robust and compact construction - weatherproof.
- ✓ Green drive technology - energy efficient motors low power consumption.
- ✓ Supplied with rubber elbow for easy fitting.




ET SERIES




ET30, ET40, ET150 & ET200



ET60, ET80, ET100, ET120, ET300



Model no.	Weight kg	Dimensions mm			
		A	B	C	D
ET30	4.0	208	150	178	14
ET40	4.3	218	156	182	14
ET60	6.0	203	165	153	18
ET80	7.0	210	185	171	18
ET100	8.5	238	196	177	18
ET120	9.5	265	215	198	18
ET150	9.0	256	200	222	18
ET200	9.0	256	200	222	18



SERVICE KITS

Model no.	Included in Service Kit		
	Diaphragm	Filter	Other
ET30-120	2	1	1 magnet
ET150-200	2	1	8 valves

At Charles Austen we recommend enviro® pumps are serviced every 18 months, service kits for each pump can be purchased from us. Sign up to our service reminder and we'll remind you when it is due!

ET30- 120 SERVICE PACKS AVAILABLE



ET150 - 500 SERVICE PACKS AVAILABLE



CONNECTIONS

ET40 - Plain, horizontal, connection 14.0mm OD also supplied with screw in barbed connector 10.0mm OD

ET60, ET80, ET100, ET120, ET150, ET200 - Plain, horizontal, connection 18.0mm OD also supplied with screw in barbed connector 12.0mm OD

ACCESSORIES

Elbow connector (included)



Large brass barbed connector 18.0mm and 20.0mm (optional)



Please note - it is important that you ensure the motor specification stated and the range of materials offered in the pump are compatible with the performance, environmental limitations and chemical resistance requirements of the application.

For further information or details of our extensive range of pumps, contact our technical sales office who will be pleased to help you select the most suitable pump for your application.

enviro[®] ETA SERIES

PRO

110V / 230V - UK/EU/USA plugin version





Model no.	Performance			Power consumption (w)	Connector Size (mm)	Dimensions (mm) (LxWxH)
	Flow (l/min)	@	Pressure (bar)			
ET40A	40	@	0.12	30	18	220x155x140
ET60A	60	@	0.12	55	18	253x165x183
ET80A	80	@	0.10	85	18	260x185x201
ET100A	100	@	0.10	105	18	288x196x207
ET120A	120	@	0.10	125	18	315x215x228
ET150A	150	@	0.20	125	18	346x200x222
ET200A	200	@	0.30	210	18	346x200x222
ET250A	250	@	0.20	220	26	348x230x219
ET300A	300	@	0.20	275	26	348x230x219

- ✓ Enviro air pump with built in alarm which detects low pressure in the airline.
- ✓ Integral high sounding buzzer and bright LED warning signals.
- ✓ Also available with 230V output wire for connection to a alarm panel or beacon.



2
YEAR
WARRANTY


*AO Versions available with 230V output cable.



ETA SERIES



ETA RANGE



Model no.	Weight kg	Dimensions mm			
		A	B	C	D
ET40A	4.3	220	155	190	14
ET60A	6.0	203	165	153	18
ET80A	7.0	210	185	171	18
ET100A	8.5	238	196	177	18
ET120A	9.5	265	215	198	18
ET150A	9.0	256	200	222	18
ET200A	9.0	256	200	222	18
ET250A	9.5	265	215	198	18
ET300A	18.5	349	231	219	18

SERVICE KITS

Model no.	Included in Service Kit		
	Diaphragm	Filter	Other
ET30A-120A	2	1	1 magnet
ET150A-200A	2	1	8 valves
ET250A-300A	4	1	16 valves

ET30A- 120A SERVICE PACKS AVAILABLE



ET150A - 500A SERVICE PACKS AVAILABLE




At Charles Austen we recommend enviro® pumps are serviced every 18 months, service kits for each pump can be purchased from us. Sign up to our service reminder and we'll remind you when it is due!



COMPATIBLE WITH OUR DIFFUSER RANGE

Please note - it is important that you ensure the motor specification stated and the range of materials offered in the pump are compatible with the performance, environmental limitations and chemical resistance requirements of the application.

For further information or details of our extensive range of pumps, contact our technical sales office who will be pleased to help you select the most suitable pump for your application.



CONNECTIONS

ET40A, ET60A, ET80A, ET100A & ET120A - Plain, horizontal, connection 18.0mm OD also supplied with screw in barbed connector 12.0mm OD

ET150A, ET200A, ET250A, ET300A - Plain, horizontal, connection 18.0mm

ACCESSORIES

Elbow connector (included)



Large brass barbed connector 18.0mm and 20.0mm (optional)



enviro[®] ET DOUBLE SERIES



REGISTERED



UK PLUG



EU PLUG



USA PLUG



110V / 230V - UK/EU/USA plugin version



Model no.	Performance		Power consumption (w)	Connector Size (mm)	Dimensions (mm) (LxWxH)
	Flow (l/min)	Pressure (bar)			
ET250	250	@ 0.20	220	26	349x231x219
ET300	300	@ 0.20	275	26	349x231x219
ET400	400	@ 0.20	347	27	340x168x247
ET500	500	@ 0.20	460	27	340x168x247

✓ Low cost, exceptionally reliable with long service intervals.

✓ UL & CE approved.



ACCESSORIES

Straight connector (included)





CONNECTIONS

ET250, ET300, ET400, ET500 - Outlet connector 26mm, also supplied with a straight rubber connector which can be used to increase pipe size to 29mm ID

Model no.	Weight kg	Dimensions mm			
		A	B	C	D
ET250	17.5	348.5	230.5	219	26.0
ET300	18.0	348.5	230.5	219	26.0
ET400	18.0	340.0	168.0	247	27.0
ET500	18.0	340.0	168.0	247	27.0

Model no.	Included in Service Kit		
	Diaphragm	Filter	Other
ET250 & ET300	4	1	16 valve
ET400 & ET500	4	1	16 valve

ET250 - 500 SERVICE PACKS AVAILABLE



At Charles Austen we recommend enviro[®] pumps are serviced every 18 months, service kits for each pump can be purchased from us. Sign up to our service reminder and we'll remind you when it is due!



enviro[®] ETX SERIES





110V / 230V - UK/EU/USA plugin version



Model no.	Performance		Power consumption (w)	Connector Size (mm)	Dimensions (mm) (LxWxH)
	Flow (l/min) @	Pressure (bar)			
ETX60 ECO	60	@ 0.15	39	18	202x177x186
ETX80 ECO	80	@ 0.15	58	18	202x177x186

✓ Low cost, exceptionally reliable with long service intervals.

✓ UL & CE approved.



CONNECTIONS

ETX60 ECO, ETX80 ECO- Outlet connector 18mm, also supplied with a straight rubber connector which can be used to increase pipe size to 18mm ID

ACCESSORIES


Elbow connector (included)



Model no.	Weight kg	Dimensions mm			
		A	B	C	D
ETX60 ECO	17.5	348.5	230.5	219	17.5
ETX80 ECO	18.0	348.5	230.5	219	17.5

Model no.	Included in Service Kit		
	Diaphragm	Filter	Other
ETX60 ECO	2	1	8 valve
ETX80 ECO	2	1	8 valve

ETX60- ETX80 SERVICE PACKS AVAILABLE



At Charles Austen we recommend enviro[®] pumps are serviced every 18 months, service kits for each pump can be purchased from us. Sign up to our service reminder and we'll remind you when it is due!



ACCESSORIES



DIFFUSERS



Coarse Bubble diffuser	100mm
Connection	19mm
Operation Temperature	0~+100°C
Material - Membrane	High grade EPDM, Silicon
Material - Support Parts	ABS

Disk Diffuser	250mm	320mm
Quantity of Bubble	6600	8300
Size of bubble	1-3mm	1-3mm
Connection	19mm	19mm
Best continuous operation	1.5 - 8.5m [^] 3/h Max: 8.5m [^] 3/h	2.5 - 15m [^] 3/h Max: 15m [^] 3/h
Operation Temperature	0~+100°C	0~+100°C
Material - Membrane	High grade EPDM, Silicon	High grade EPDM, Silicon
Material - Support Parts	ABS	ABS

Straight air diffuser	250mm	500mm	1000mm
Quantity of Bubble	4000	8300	18000
Size of bubble	1-3mm	1-3mm	1-3mm
Connection	19mm	19mm	19mm
Best continuous operations	1.5 - 6.7m [^] 3/h Max: 6.7m [^] 3/h	2.5 - 11.3m [^] 3/h Max: 11.3m [^] 3/h	5 - 24m [^] 3/h Max: 24m [^] 3/h
Operation Temperature	0~+100°C	0~+100°C	0~+100°C
Material - Membrane	High grade EPDM, Silicon	High grade EPDM, Silicon	High grade EPDM, Silicon
Material - Support Parts	PVC	PVC	PVC

- ✓ Fine bubble and coarse bubble options
- ✓ Designed for use with the ET range of pumps



ENVIROSURE ALARM


Model no.	Description	Part Number
envirosure 100	Alarm module	A07-001
envirosure 120	Alarm module with beacon & inline transformer	A07-006



- ✓ Envirosure detects low pressure alerting the user of pump failures or power cuts immediately.
- ✓ Versatile installation - Takes minutes to install.
- ✓ Multiple variants- options include bright LED beacon, plugin or hardwire

MANIFOLDS

Model no.	Description	Outlet sizes	Inlet sizes
4 Way	Steel	4	18
6 Way	Steel	4	18
8 Way	Steel	4	18
10 Way	Steel	4	18
12 Way	Steel	4	18
18 Way	Steel	4	18
24 Way	Steel	4	18



- ✓ Custom sizes available.
- ✓ Allow several processes to be run from the same pump.
- ✓ Allow numerous air stones or air curtains to be connected in a hydroponic tank and aquarium.

TUBING


Model no.	Length	Size Ø
Braided Tubing	80m	18mm
	100m	18mm
	100m	8mm
Silicone Tubing	200m	6x4mm
	100m	8x4mm
	100m	8mm
Black Tubing	200m	4x6mm
Bubbler Tubing	200m	4mm
	50m	4mm



SILICONE TUBING



BUBBLER TUBING



BRAIDED TUBING

- ✓ Designed to connect manifolds if multiple air stones/ diffusers.
- ✓ Connects water and air pumps to an air stone.




ORDERING

Phone our order & product enquiry hotline:

+44 (0)1932 355277

Email your order to:

enquiries@charlesausten.com



For more product information and a look at our entire range of pumps you can visit our website:

www.charlesausten.com

CHARLES AUSTEN PUMPS LTD

Royston Road,
Byfleet,
Surrey,
KT14 7NY, UK

BLUE DIAMOND PUMPS INC

5072 Bristol Industrial Way
Buford,
GA 30518,
USA

WARRANTY

All Enviro[®] pumps are covered by a two year warranty on the pump motor. To validate this warranty, the aerator must be serviced on a yearly basis. We recommend that the consumables including the diaphragms and filter are changed at this point.

The wear and tear parts are outside the two year warranty but are covered by a year's warranty providing they have been used correctly and not subjected to back pressure or water damage.

This warranty is only valid for pumps that are used as recommended.

2
YEAR
WARRANTY



APPLICATIONS





For almost three-quarters of a century, Charles Austen Pumps has revolutionized many different markets through its design innovation but also its world-wide distribution network, and during that time has gained the respect and trust of industries throughout.

Charles Austen Pumps Ltd stocks an extensive range of linear aeration pumps and accessories suitable for use in wastewater applications alike. The range incorporates air pumps with varying flow rates. All of our pumps are built with thermal cut out with safety trip switch.